<u>Home > Advisory services > Video Technology Advisory Service > Product evaluations > Product evaluation reports > Radvision XT5000 > Appendix 3 - Radvision XT5000 - Detailed audio test results</u>

Appendix 3 - Radvision XT5000 - Detailed audio test results

Test 1: Frequency response (-3 dB)

(Insert -6 dB signal at local site, measure at remote site)

<u>G.711 A law</u>	<u>G.722.1</u>	AAC-LD,	<u>G.719</u>
4.2 KHz	7.0 KHz	14.5 KHz	20.0 KHz

Test 2: Headroom (measured on AAC-LD signal coding)

Insert increasing amplitude 1 KHz tone at local site, monitor for overload distortion at remote site

Overload occurs at: +9dBm

Test 3: Audio level

(Insert -6dBm 1KHz tone at local site, monitor received level at remote site.)

As the audio output level is affected by the volume control this test was not carried out.

Test 4: Echo Cancellation

<u>Setup</u> The echo canceller is fully automatic in operation. The quality of echo cancellation and doubletalk from the system was excellent.

	Lecture Theatre	Room
Audio levels adequate? (Yes/no)	Not tested	Yes
Audio quality acceptable? (Yes/no)	Not tested	Yes
Echo cancellation acceptable? (Yes/no)	Not tested	Yes

Source URL: https://community.jisc.ac.uk/library/appendix-3-radvision-xt5000-detailed-audio-test-results