

Appendix 1 - Lifeseize Icon 600 - Detailed Physical Information

Dimensions of the CODEC: (w x h x d) 37 x 4.4 x 16 cm

Video Inputs	<u>Type</u>	<u>Connector</u>
Main HD camera	Digital	HDMI
PC	Digital/AnalogRGB	DVI-I

Video Outputs	<u>Type</u>	<u>Connector</u>
Main monitor	Digital	HDMI*
Dual monitor	Digital	DVI-I

* The Main Monitor HDMI* output includes embedded digital audio.

Audio Inputs	<u>Level</u>	<u>Connector</u>
Digital MicPod™	Digital	Mini USB
External microphone input with echo canceller	Mic/Line	Mini jack

HDMI	Digital	HDMI
DVI-I	Digital	DVI-I

Audio Outputs	<u>Level</u>	<u>Connector</u>
Main audio left and right	Digital	HDMI
Main audio left and right	Line	Mini jack

Data

1. 1 off LAN 10/100 Mbits/s Ethernet connection (RJ45)
2. 2 off USB slot (future use)

Cables Supplied

1. 1 off 3 metre, HDMI-HDMI camera cable
2. 1 off 3 metre, HDMI-HDMI monitor cable
3. 1 off 3 metre, HDMI-DVI-I monitor cable
4. 1 off 3 metre, 15 pin HD D Type male – DVI-I PC input cable
5. 1 off 3 metre, RJ45-RJ45 Ethernet cable

Mobility

The LifeSize Icon 600™ system is portable, lightweight and can be moved easily. To establish a connection DHCP would normally be used to allocate network settings.