

CODEC Test procedure

PROCEDURES & RESULT TABLES

Reference: GD/VTAS/012

Version: 1.46

Date: 17.12.2012

Authors: Paul Down Freelance Author, Jim Sheach, Urwin Wood,
Learning and Teaching Spaces Technology Section (LTSTS),
The University of Edinburgh, <http://www.ed.ac.uk/is> ^[1]

- **1. OVERVIEW**
- **2. EQUIPMENT TEST PROCEDURE**
 - 2.1 Vision Signal Tests
 - 2.2 Audio Signal Tests
 - 2.3 Data Transfer
 - 2.4 Ease of Use
 - 2.5 Standards Conformance - Inter-working
 - 2.6 Network Connections
- **3. TABLES**

- 3.1 Video Performance
- 3.2 Recording Devices
- 3.3 Streaming Devices
- 3.4 Audio Performance
- 3.5 Data Transfer
- 3.6 Interoperability

- **4. IMPORTANT FACTORS/CONSIDERATIONS**

GENERAL

- 4.1 Ease of Use
- 4.2 Value for Money
- 4.3 Multi-Vendor Solutions
- 4.4 High Definition Capability
- 4.5 Wide Screen Formats
- 4.6 Television Scanning and Aspect Ratios 720i, w1080p etc.
- 4.7 Interlaced CIF (iCIF)

VIDEO

- 4.8 Video Coding
- 4.9 Dual Video Streams
- 4.10 Picture Optimisation

AUDIO

- 4.11 Audio
- 4.12 Advanced Audio Coding (AAC-LC, AAC-LD)

NETWORK

4.13 IP Video Tests

4.14 Network/Dialling

4.15 Session Initiation Protocol (SIP)

4.16 Dynamic Host Configuration Protocol (DHCP)

4.17 802.11 b/g Wi Fi

4.18 API Commands

4.19 BFCP Binary Floor Control Protocol

4.20 SSH Secure Shell Protocol

DATA SHARING

4. 21 Data Transfer/Application Sharing

FEATURES

4.22 On Board Multipoint Control Units (MCUs)

4.23 Remote Camera Control/Source Selection

4.24 Auto Tracking Cameras

4.25 Encryption

4.26 Picture on Picture (Chroma-Key)

4.27 High Bandwidth Digital Content Protection (HDCP)

INTERFACES AND CONTROL

4.28 Digital Video Interface (DVI)

4.29 Analogue Component Interface YPbPr

4.30 Extended Display Identification Data (EDID)

4.31 The Sony Philips Digital Interface (SPDIF)

4.32 VISCA

- **5. TRADEMARKS AND ACKNOWLEDGEMENTS**

- **5.1 Trademarks**

- 5.2 Further Acknowledgements

1. OVERVIEW

The Video Technology Advisory Service (VTAS) undertakes a number of technical studies including the evaluation of videoconferencing equipment. The main goal of this evaluation is to provide objective advice for higher and further education and research organisations so that they may make informed choices when purchasing videoconferencing equipment for use over IP (Internet Protocol), ISDN (Integrated Services Digital Network), and other networks.

To enable conferencing between more than two sites, the JANET Videoconferencing Service (JVCS) provides multipoint facilities for both ISDN and IP networks enabling multi-site communications between suitably equipped conference rooms and desktop systems. To be compatible all equipment must conform either to the ITU-T (International Telecommunications Union - Telecommunications Standardization Section) H.320 series of recommendations implemented for transmission over the ISDN switched system or to the ITU-T H.323 series of recommendations for transmission over IP networks.

Videoconferencing systems comprise:

- **Input Devices** - Microphones, television cameras, white boards, etc. that provide the sound, vision and data input signals.
- **Coding-Decoding Equipment** - The CODEC (COder-DECoder) that provides the analogue/digital interface for the input devices, the digital/analogue interface for the output devices and all the compression and signal processing necessary.
- **Output Devices** - Loudspeakers, television picture monitors or data screens, white boards, etc. that generate the sound, vision and data output information at each site.

Recording Devices may also be used. Some, such as the Codian IP VCR, allow a conference to be recorded for later transmission or viewing either as a point to point, multipoint or a streamed conference.

There is a wide range of equipment on the market, matched by a wide variation of needs across the JANET community. The three main categories are:

- **Room-based Systems** - Full facilities, ISDN2 - ISDN30 and IP network capability. Prices from £5,000. Not designed to be moved.
- **Desktop Systems**
 1. A plug-in card for a PC can provide ISDN and IP interfaces. USB connected devices can provide IP-only interfaces which may easily be moved between host PCs or laptops, these devices are Windows only. Prices 400 - 600 (plus the cost of the PC).
 2. Fully integrated desktop conferencing systems including camera, picture monitor and loudspeakers in a single convenient package

Some overlap occurs between categories, e.g. some sophisticated PC based systems may be mounted on a trolley with a large television picture monitor and marketed as a roll-about or room system. In this document, compact portable CODECs are included with the room

based systems, but it is worth noting that these compact portables are slightly different - they generally offer limited facilities for a relatively low cost.

The growth of interest and demand for videoconferencing generally in the JANET community, combined with the multipoint facilities of the JVCS, has created a need for objective advice on products that are standards compliant and able to work effectively in the JVCS environment.

Equipment may be offered to operate over a variety of networks. ISDN and IP systems require their own compression algorithms to achieve transmission, e.g. ISDN requires equipment conforming to the ITU-T H.320 standard whereas IP requires equipment to the ITU-T H.323 recommendations. Some products use other compression algorithms e.g. MPEG-1 (Moving Pictures Expert Group) and MPEG-2. Although these products are not supported by JVCS, non-standard equipment will still operate point-to-point, and so if conferencing is only required between two sites, e.g. between sites on a split campus, then these could be a possible choice. With High Definition (HD) capable products there is now a growing trend for products to be offered in IP only configuration.

The list of manufacturers represented here is not exhaustive. VTAS would be pleased to consider suggestions for future products and suppliers although the in-depth evaluation of equipment is a time consuming process and VTAS is currently only able to test a limited number of products each year. The presence of a product in this list indicates only that the product has been evaluated by the VTAS product evaluation team, and should not be taken as a recommendation. Similarly, the absence of a popular product from the list should not be seen to reflect negatively on that product.

The evaluation process produces a snapshot of the features and performance of a product at a specific moment in time. It is worth noting that a significant period of time may have elapsed between the date of testing and the time of reading this report, and during this period some products may have been updated by the manufacturer or even superseded. Full technical specifications of all the products evaluated (together with many others) are included in the manufacturers' web sites. It is strongly recommended that these sites be read in conjunction with the test reports and their associated comments, so that a more complete assessment of a product is obtained.

Conferencing equipment is only one of the components necessary for videoconferencing. The effective and efficient use of videoconferencing is also dependent on the room environment, the network, booking procedures, etc. For further information see other material available on this site.

2. THE EQUIPMENT TEST PROCEDURE

The evaluations are conducted at the University of Edinburgh. Testing extends to connectivity with the Multipoint Control Unit (MCU) facilities of the JANET Videoconferencing Switching Service (JVCSS) including the JVCSS Codian High Definition (HD) MCU and the JVCSS MGC Standard Definition (SD) MCU that are located across the JANET network.

The procedure was designed to test most aspects of the CODEC. Tests are carried out at IP 384, 768 kbit/s and higher speeds such as 1Mbit/s, 2Mbit/s, 4Mbit/s and higher if these are available. If the CODEC also offers ISDN connectivity then this will be evaluated at 128, 384

and 768 kbit/s. Other coding standards e.g. MPEG-1, MPEG-2 will also be tested at appropriate data rates. The Current trend for the most popular products is to only offer IP connectivity, with ISDN sometimes available as an option. High Definition (HD) systems will also be tested in their appropriate wide screen formats i.e. w1080p, w720p, w448p, w228p etc.

Technical considerations such as audio quality and vision quality are paramount, and the ability to transfer data transparently is a desirable feature. However, just as important for the user, especially non-technical staff is the ease of setting up and operating the equipment, dialling the remote site and the reliability of connections during a conference.

The American National Standards Institute (ANSI) has carried out extensive objective and subjective assessments of image degradation during videoconferencing. For our test procedure we used similar images to those described in the ANSI document *Video test scenes for subjective and objective performance assessment in videoconferencing* (ANSI 801.1).

In order to minimise possible variations between different assessors, it was decided that only one site would carry out subjective impairment tests. All tests were conducted using a standard test tape at both sites. The tape included:

- test signals to check system gain and a selection of scenes typical of videoconferencing, e.g. talking heads, nodding heads, slow and fast zooming, close ups and wide angle shots;
- images which allow us to test the legibility of text (various sizes) and a large map;
- a person teaching at a flip-chart;
- a moving football (off air) sequence.

Jerkiness was assessed by a method devised specifically for this evaluation. A test pattern comprising blocks of colour joined by spokes of a wheel was rotated at four fixed synchronous speeds on a record turntable (driven from a tone oscillator through a power amplifier). Any jerkiness in the images was immediately apparent.

The test procedure can be summarised as follows. The complete test schedule is set out in Appendix A [2].

2.1 Vision Signal Tests

Objective signal levels are measured using analogue test signals to verify that vision gain settings are accurate and that the colour information is not degraded unduly. For PC based CODECs where external connections are not provided it is not possible to conduct all of the tests, in these products cameras feed directly into the PC USB (Universal Serial Bus) port and the received signals are fed directly to the PC Visual Display Unit (VDU). In these cases the test tape can not be viewed so the only method of judging the vision quality is by subjectively assessing the normal conference video through the PC screen. It is possible that additional signal degradation could be introduced by the PC VDU. This potential extra source of degradation is outside of the scope of the testing procedure. A series of subjective vision assessments are then carried out by referring to an agreed scale of degradation:

Imperceptible	1
Perceptible	2
Slightly annoying	3
Annoying	4
Very annoying	5

The following specific impairments were assessed where appropriate:

- lip synchronisation (LS);
- block distortion (tiling) (BLK);
- blurring (BLR);
- colour errors (CLR);
- jerkiness (distortion of smooth motion) (JRK);
- object persistence (image retention from a previous frame) (OP);
- scene cut response (time to build up a new image) (SCR).

2.2 Audio Signal Tests

Where appropriate, frequency response and headroom (i.e. the capacity for signal overload or peaks) are measured for the following audio standards:

Standard	Data rate
----------	-----------

G.711 (nominal bandwidth 3.5kHz)	48, 56 or 64kbit/s
G.719 20Khz Bandwidth Full bandwidth music quality	32-128 Kbit/s (Mono) 64-256 Kbit/s (Stereo)
G.722 (nominal bandwidth 7kHz)	48, 56 or 64kbit/s
G.728 (200-3.4KHz) Speech quality	16 Kbit/s very low delay
G.729 high quality low bandwidth speech	8 Kbit/s
MPEG-4 AAC-LD	64 kbit/s and 128kbit/s
MPEG-1 Layer III (MP3)	Normally 128kbit/s

The G.728 standard is important for low data rate conferences (i.e. ISDN 2, 128kbit/s) to allow adequate bandwidth for the vision signal.

For MPEG-1 and MPEG-2 products, the appropriate audio coding standard is tested e.g. ISO/IEC 11172-3 Layer II 16bit 48kHz Stereo.

MPEG-4 AAC-LD coding achieves high quality with a low transit delay (latency) during a conference and has both 64kbit/s and 128 kbit/s coding standards.

Some manufacturers provide proprietary audio coding, to achieve extended frequency response, but this does require each site to have the appropriate coding within the CODECs.

Siren 14.24 (nominal bandwidth 14 kHz)	H.320 data rate 128 kbit/s
Siren 14.32 (nominal bandwidth 14 kHz)	H.320 data rate 384 kbit/s
Siren 14.48 (nominal bandwidth 14 kHz)	H.323 up to 4Mbit/s

Siren 22 (nominal bandwidth 22KHz)	H.323 either 48 Kbit/s or 64 Kbit/s
------------------------------------	-------------------------------------

To ensure products will work effectively through the JVCS MCU service an additional audio level check is carried out. A connection is made to the JVCS management centre and the received audio level on normal speech is measured. A received level peaking between 0dBm to +4 dBm is acceptable. This test is identical to that carried out for a pre-registration QA test.

The operation of echo cancellers is tested in some detail, in both a conference room and in the more demanding environment of a small lecture theatre seating 100.

As for the video tests some Desktop products are not provided with external audio output connections so objective measurements cannot be taken.

2.3 Data Transfer

Products can offer a variety of methods of transferring data between sites. The original ITU-T recommendation for data interchange over H.320 and H.323 was T.120 but this is now rarely used as its use could degrade the sound or vision signals. Other methods are now preferred e.g. a separate signal as in H.239 Dual channel transmission or alternatively using the Internet and a proprietary software link. These methods enable data from a PC to be incorporated into a conference.

2.4 Ease of Use

This is considered a prime requirement so several aspects are assessed:

- quality of documentation;
- type and method of connections to peripheral equipment;
- set-up procedure;
- methods of operation, i.e. remote controls, menus, etc;
- portability of equipment.

2.5 Standards Conformance - Inter-working

If the unit is in any way incompatible in either point-to-point or multipoint situations, then a conference may not be successful. Both point-to-point compatibility and compatibility through the JVCS MCUs are examined. It is rare for complete compatibility to occur between different manufacturer's products although in many cases the incompatibilities are fairly minor e.g. a reduction in the resolution of the pictures. This still permits a conference to be effective albeit not at the optimum achievable quality.

2.6 Network Connections

In this section, the ease of dialing a remote site on ISDN2 and ISDN6, or the ease of storing and recalling IP/DNS addresses is examined. The effect of losing one circuit on an ISDN6 call is also examined. The IP connection is deliberately disconnected and reconnected to simulate a connection failure. The time the CODEC requires to re-establish the conference is then measured.

2.6.1 ISDN Networks

ISDN switched networks provide Guaranteed Quality of Service (GQoS). For all intents

and purposes the network can be viewed as transparent (up to the bandwidth provided). If an ISDN6 (384kbit/s) circuit is dialled then 384kbit/s can be relied on to be available continuously for the duration of the conference. Creating a reliable connection between ISDN sites is not always straightforward. Different manufacturers approach the method of connection in various ways. If the conference system is 'intelligent' it will iron out many of these difficulties and make connection easier and more reliable.

2.6.2 IP Networks

IP connections over LANs (Local Area Networks), MANs (Metropolitan Area Networks) and WANs (Wide Area Networks) using H.323 compliant equipment may not provide a Guaranteed Quality of Service. This means that during a conference the operational bandwidth may or may not be provided for some or all of the time. IP networks normally carry a significant amount of other data traffic so the quality of the circuit provided will depend on the density and frequency of this competing traffic. The effect of bandwidth being robbed from the IP videoconferencing connection can be quite dramatic. At its worst the intelligibility of the sound can be lost and the picture can break up completely. Some networks can prioritise IP for specific types of traffic including videoconferencing. Another approach is to provide so much bandwidth over the network that saturation cannot occur, however this is an expensive solution. During VTAS testing of IP products the network is optimised by eliminating local bottlenecks i.e. CODECs are connected directly to network routers to avoid congested local networks. This **does not** represent a typical IP network but does enable the limiting audio and video performance of the CODEC alone to be realistically assessed without other factors interfering.

3. SUMMARY TABLES

The results of the products tested are summarised in the tables below. Full results of the tests are detailed in the individual product test reports. To make comparison more meaningful for prospective purchasers, only recent products tested will be shown together with those tested during the preceding two years. Older products tested are included for reference under [ARCHIVE](#) [3].

3.1 Video Performance

Sixteen separate tests were carried out, involving test signals and scenes typically found during a videoconference. Where fitting, each test was used to assess blocking, blurring, jerkiness, colour response, persistence and scene cut response. Testing was carried out at ISDN data rates of 128kbit/s - 384kbit/s and for data compression algorithms H.261, H.263, H.264, and up to 60 frames per second (fps) options, as appropriate. For those products with H.323, i.e. IP, CODECs tests were repeated at IP 384kbit/s - 8Mb/s, as appropriate. For MPEG-1 products, data rates appropriate to the equipment were tested. A quick comparison of video performance can be made from the summary tables below.

The summary table scores were obtained by first calculating the sum of all scores for each particular test, (e.g. for test 1, adding figures for blocking, blurring, jerkiness and colour response), and then combining the totals for tests 1 - 15. The lower the score, the better, so a perfect product, scoring 1 for each measurement, would have produced a total score of 67 in the table. While not giving the whole picture (i.e. indicating the performance of individual products in a particular test such as fast moving images), the table does provide a very useful indicator to overall video performance and is in line with overall subjective impressions. The Tables should be examined closely as rather contrary to expectation not all

the latest products perform better than products they replace. The 'Category' classification indicates whether the product is a room-based (R), or PC-based (PC) solution.

Table 1 H.320 (ISDN) Video Performance							
	128kbit/s			384kbit/s			Category
	H.261	H.263	H.264	H.261	H.263	H.264	
Aethra Vega X3	205	199	188				R
Tandberg 990 MXP	185	182	153	126	117	104	R

Table 2 H.323 (IP) Video Performance

H.261		384kbit/s	768kbit/s	1Mbit/s	2Mbit/s	4Mbit/s
Aethra Vega X3		150	122		88	
AVermedia AVercomm H300		187	156		122	
Avermedia HVC330		181	157		118	
Radvision Skopia XT1000			124		105	
Radvision Skopia VC240		See	Test	Report		

Sony PCS-XG80		128		98	
Tandberg 990 MXP	126	104		83	
<i>HDTandberg Profile6000MXP</i>	<i>132</i>	<i>104</i>	<i>94</i>	<i>87</i>	
ZTE ZXT500	131	108		89	

Table 3 H.323 (IP) Video Performance

H.263	384kbit/s	768kbit/s	1Mbit/s	2Mbit/s	4Mbit/s
Aethra Vega X3	136	103		81	
AVermedia AVercomm H300	162	130		114	105
Avermedia HVC330	155	123		105	98
Radvision Skopia XT1000		133		111	105
Radvision Skopia VC240	See	Test	Report		
Radvision XT5000	130	105		91	87 857

Sony PCS-XG80			115		93	85
Tandberg 990 MXP		116	97		78	
<i>HD Tandberg Profile 6000MXP</i>		124	95	82		75
<i>Tandberg Edge 95 MXP(2008)</i>		145	117		99	
ZTE ZXT500		118	86		78	

H.264	384kbit/s	768kbit/s	1Mbit/s	2Mbit/s	4Mbit/s	8Mbit/s
Aethra Vega X3	121	96				
AVermedia AVercomm H300	160	120		103	93	
Avermedia HVC330	155	121		105	97	
Cisco Telepresence EX60	112	88		76	71	70(5)
Cisco SX20 Quick Set	112	93		78	73	70(5)

<i>HD LifeSize RoomT</i>	123	104	95	75 (2)		
<i>HD LifeSize TeamT</i>	120	100	91	82 (2)		
<i>HD LifeSize Express</i>	124	100	97	85		
<i>LifeSize Room 200</i>	121	101		87	78	77 (5)
<i>LifeSize Passport (6)</i>	See	Report	For	Results		
<i>LifeSize LGExecutive (6)</i>	See	Report	For	Results		
<i>Lifesize –Team220</i>	119	98		83	78	73 (5)
Polycom HDX 9004	132	114	103	95	89	
Polycom HDX 8004	143	109		88	79	
Polycom QDX 6000	136	128	116	100		
Polycom HDX 9004	120	98		83	76	
Polycom HDX 4500	145	107		86	76	

Radvision Skopia XT1000		99		85	78	
Radvision Skopia VC240		See	Test	Report		
Radvision XT5000	114	95		82	77	737
Sony PCS-G70P	113	90			82	
<i>HD Sony PCS- HG-90</i>				91	73	69
<i>Sony PCS- XG80 4</i>		102		82	77	75 (74) 4
Tandberg 990 MXP	111	83		86		
<i>Tandberg Edge 95 MXP(2008)</i>	148	120		100		
<i>HD Tandberg Profile6000MXP</i>	122	96	88	74		
<i>Tandberg 3 FieldView™</i>	122*	138*	127*	92*		
<i>Tandberg C60</i>	111	89		80	85	79

<i>Tandberg C20 Plus</i>	107	87		79	75	73(5)
<i>Tandberg C40</i>	102	91		79	75	75(5)
ZTE ZXT500	108	91		74		
H.264	384kbit/s	768kbit/s	1Mbit/s	2Mbit/s	4Mbit/s	8Mbit/s

High Definition CODEC's identified by HD Prefix

1. *Tandberg 6000 CODEC scores at 3Mbit/s not 4Mbit/s*
2. *LifeSizeRoom and Team CODECs score at 2.5Mbit/s not 2 Mbit/s*
3. *Tandberg Fieldview™ scores at maximum bit rates of 300kbit/s, 500kbit/s, 1.2Mbit/s and 2.5Mbit/s See report for more details*
4. *Sony XG80 scores at both 8 Mbit/s and 10 Mbit/s*
5. *Cisco Telepresence EX60 and SX20, Lifesize 200, Lifesize 220 ,Tandberg C20 Plus and Tandberg C40 score at 6 Mbit/s not 8 Mbit/s*
6. *The LifeSize Passport and LifeSize LGExecutive are not provided with external video inputs*
therefore detailed testing could not be carried out
7. **Radvision XT5000 tests at 6 Mbit/s**

3.2 Recording Devices

To assess the transparency of recording devices, comparative tests were carried out. Subjective scores were taken for the direct point-to-point link and then a playback from the recording device, as outlined below:

- A point-to-point connection between a Tandberg 6000 and a Polycom VSX8000.
- A recording from the Tandberg 6000 to the RSS2000 and then replayed from the RSS 2000 to a Polycom VSX 8000.

All devices were set to auto-negotiate audio and video protocols.

Table 4 H.323 (IP) Video Performance of Recording Devices

Recording Device	384kbit/s		768kbit/s		2Mbit/s	
	Point-to-point	Recording	Point-to-point	Recording	Point-to-point	Recording
Codian IP VCR 2210	124	131	103	109	81	84
Polycom RSS 2000	128	138	99	102	78	81

3.3 Streaming Devices For streaming devices such as the Tandberg Content Server and FieldView that record H.323 conferences and then live-stream, archive and subsequently replay the conferences as a media stream it may not be possible to conduct all of the normal CODEC video, audio and data tests. Refer to the relevant test report for more detailed information.

3.4 Audio Performance

Echo cancellation is essential for hands free, natural videoconferencing, i.e. without the use of telephone handsets or headphones. Large lecture theatres can be very reverberant so efficient echo cancellation is necessary for good results. In the past a separate, external echo canceller was recommended for good results, but as CODECs now generally incorporate excellent echo cancellation within the unit, a separate echo canceller may not be necessary. The ability for both sites to converse simultaneously is referred to as double talk. This is the natural way to conference, but efficient echo cancellation is needed in order to enable double talk. Most of the products achieving a good or better score under echo cancellation in Table 4 enabled effective double talk in a small conference room and some performed well in a small lecture theatre (100 seats). This issue is examined in greater detail in section 4.7, Audio.

Table 5 Audio Performance					
	Audio Quality	Special Audio coding	Echo Cancellation	Audio Level	Software available ()

Aethra Vega X3	Satisfactory	MPEG-4 AAC-LD	Excellent	Satisfactory	
AVermedia AVercomm H300	Lip Synchronisation problems		Very good	satisfactory	
Avermedia HVC330	Lip Synchronisation Problems Non linear frequency response		Problems	satisfactory	
Cisco Telepresence EX60	Very Good	MPEG-4 AAC-LD Stereo	Excellent	Satisfactory	
Cisco SX20 Quick Set	Very Good	MPEG-4 AAC-LD Stereo	Excellent	Satisfactory	
Codian IP VCR 2210	Some problems	Siren 14, AAC-LC, AAC-LD	N/A	Satisfactory	
LifeSize RoomT	Acceptable	MPEG-4 AAC-LD	Excellent	Satisfactory	
LifeSize TeamT	Very good	MPEG-4 AAC-LD, Siren 14	Excellent	Satisfactory	
LifeSize Express	Very Good	MPEG-4 AAC-LD, Siren 14	Excellent	Satisfactory	

LifeSize Room 200	Very Good	MPEG-4 AAC-LD, Siren 14	Some problems	Satisfactory	
LifeSize Passport	Good when close to the microphone	MPEG-4 AAC-LD,	Good	Satisfactory	
<i>LifeSize – Team220</i>	Very Good	MPEG-4 AAC- LD, Siren 14	Very good	Satisfactory	
<i>LifeSize LGExecutive</i>	Good when close to the microphone	MPEG-4 AAC-LD,	Excellent	Satisfactory	
Tandberg FieldView™	Good	MPEG-1	Good	Satisfactory	
Polycom HDX 9004	Very good	Siren	Excellent	Satisfactory	Y
Polycom RSS 2000	Acceptable		N/A	Satisfactory	
Polycom HDX 8004	Very Good	Siren 14 & 22	Excellent	Satisfactory	
Polycom QDX 6000	Some problems with lip synchronisation	Siren 14 & 22	Acceptable	Satisfactory after adjustment	
Polycom HDX 9004	Some problems with Lifesize CODECS	Siren 14 & 22	Excellent	Satisfactory	

Polycom HDX 4500	Frequency response notch at 7 KHz But good	Siren 14 & 22 Polycom® StereoSurround™.	Excellent	Satisfactory	
Radvision Skopia XT1000	Good But care needed with interfacing equipment	MPEG-4 AAC-LD G.719	Excellent	Satisfactory	
Radvision Skopia VC240	Some problems	G.729	Excellent	Satisfactory	
Radvision XT5000	Good	MPEG-4 AAC-LD Optional G.728, G.729A	Excellent	Satisfactory	
Sony® PCS- HG90	Good	MPEG4 AAC-48K MPEG4 AAC-96K	Good	Satisfactory	
Sony Contact 6000	Acceptable		Fair	Low	
Sony PCS- XG80	Very good	MPEG-4 AAC	Very Good	Satisfactory	
Tandberg 990 MXP	Good	MPEG-4 AAC-LD	Excellent	Satisfactory	
Tandberg Edge 95 MXP(2008)	Good	MPEG-4 AAC-LD	Good	Satisfactory	

Tandberg Profile 600MXP	Some problems	MPEG4 AAC-LD	Good	Satisfactory	
Tandberg C60	Good	MPEG4 AAC-LD	Excellent	Satisfactory	
Tandberg C20 Plus	Good	MPEG4 AAC-LD	Excellent	Satisfactory	
Tandberg C40	Good	MPEG4 AAC-LD	Excellent	Satisfactory	
ZTE ZXT500	Good	Siren (3)	Good	Satisfactory	
	Audio Quality	Special Audio coding	Echo Cancellation	Audio Level	Softv pa availa (

About this table

1. A patch is available from Polycom. Please contact your local supplier.
2. A high frequency whistle was experienced with the equipment on test but subsequent checking by Tandberg UK could not reproduce the problem.
3. Although Siren Audio was specified only G.722 could be achieved during testing.

3.5 Data Transfer

Table 6 Data transfer	
	Comments
Aethra Vega X3	Using the Aethra software, AePPTManager, PowerPoint presentations could be transmitted to the remote site as a series of still images only. T.120 also supported.

AVermedia AVercomm H300	Data may be introduced via the VGA interface
Avermedia HVC330	Data may be introduced via the VGA interface And over the net using ScreenShare software
Cisco Telepresence EX60	Data may be introduced via the DVI-I interface
Cisco SX20 Quick Set	Data may be introduced via the DVI-I interface
Codian IP VCR 2210	N/A
LifeSize RoomT	Data may be introduced via the VGA interface.
LifeSize TeamT	Data may be introduced via the VGA interface.
LifeSize Express	Data may be introduced via the VGA interface.
LifeSize Room 200	Data may be introduced via the DVI-I interface
LifeSize Passport	H.239 data via LifeSize Virtual Link software
LifeSize LGExecutive	H.239 data via LifeSize Virtual Link software

<i>Lifesize – Team220</i>	Data may be introduced via the DVI-I/VGA interface
Polycom HDX 9004	DVI interface for PC connection.
Polycom RSS 2000	N/A
Polycom HDX 8004	A DVI-I interface for PC connection
Polycom QDX 6000	VGA input or via a network connection using People and Content IP™.
Polycom HDX 9004	A DVI-I interface for PC connection
Polycom HDX 4500	A DVI-I interface for PC connection People + Content™ software may also be used to connect a PC via IP
Radvision Skopia XT1000	DVI interface for PC connection
Radvision Skopia VC240	DVI and VGA PC interfaces
Radvision XT5000	DVI and VGA PC interfaces
Sony Contact 6000	Data sharing achieved over both H.320 and H.323 networks.
Sony® PCS-HG90	Data may be introduced via the VGA interface.

Sony PCS-XG80	Data may be introduced via the VGA interface.
Tandberg 990 MXP	Data sharing via Soft Presenter/Virtual Computer Network or direct via CODEC DVI-I interface.
Tandberg Edge 95MXP (2008)	Data sharing via Soft Presenter/Virtual Computer Network or direct via CODEC DVI-I interface
Tandberg Profile 600MXP	Data sharing via Soft Presenter/Virtual Computer Network and T120 or direct via CODEC DVI-I interface
Tandberg FieldView™	No data sharing but images may be annotated. See report
Tandberg C60	VGA and DVI interfaces for PC
Tandberg C20 Plus	VGA and DVI interfaces for PC
Tandberg C40	VGA, Analogue Component and DVI interfaces for PC
ZTE ZXT500	T.120 supported

3.6 Interoperability

All models tested conferenced satisfactorily with another identical unit. This test specifically checks the performance of the CODEC with units from other manufacturers and also through the JVCS MCUs. The VBrick 3000/6000 could not be tested for inter-working as no other products operating to the MPEG-1/MPEG2 standards were available at the testing sites.

Table 7 H.320 (ISDN) Inter-working Performance

	With Another CODEC	Multipoint Conference through JVCS	MCU Control	Far End Camera Control
Aethra Vega X3	Satisfactory	Satisfactory	No	Yes (2)
Codian IP VCR 2210	Some problems	Satisfactory	N/A	N/A
Sony Contact 6000	Some problems	Satisfactory (1)	Yes	Yes
Tandberg 990 MXP	Some problems	Satisfactory	No	Yes

About this table

Where "some problems" is indicated in the table please refer to the detailed test report for the relevant CODEC.

1. No problem with connecting, but audio level low (see Audio Test).
2. Far-end camera control and remote source selection.

Table 8 H.323 (IP) Inter-working Performance **

	With Another CODEC	Multipoint Conference through JVCS	MCU Control	Far End Camera Control
Aethra Vega X3	Some problems	Satisfactory	No	Yes (1)
AVermedia AVercomm H300	Satisfactory	Satisfactory	No	Yes

Avermedia HVC330	Satisfactory	Satisfactory	No	Yes
Cisco Telepresence EX60	No compatibility problems encountered	Satisfactory	No	Yes
Cisco SX20 Quick Set	No compatibility problems encountered	Satisfactory	No	Yes
LifeSize RoomT	Some problems	Some problems	No	Yes
LifeSize TeamT	Satisfactory	Satisfactory	No	Yes
LifeSize Express	Some problems	Satisfactory	No	Yes(1)
LifeSize Room 200	Some problems	Satisfactory	No	Yes
LifeSize Passport	Some problems	Satisfactory	No	Yes
LifeSize LGExecutive	Some problems	Some problems	No	Yes
<i>Lifesize – Team220</i>	Minor problems	Satisfactory	No	Yes
Polycom HDX 9004	Some problems	Satisfactory	No	Yes (1)

Polycom RSS 2000	Some problems	Satisfactory	N/A	N/A
Polycom HDX 8004	Some problems	Satisfactory for both standard and High definition signals	N/A	Yes (1)
Polycom QDX 6000	Minor problems	Satisfactory	No	Yes (1)
Polycom HDX 9004	Some problems	Satisfactory for both Standard and High Definition signals	No	Yes(1)
Polycom HDX 4500	Satisfactory	Satisfactory	No	Yes
Radvision Skopia XT1000	Some problems	Satisfactory	No	Yes
Radvision Skopia VC240	Some problems	Some minor problems	No	No
Radvision XT5000	No compatibility problems encountered	Satisfactory	No	Yes
Sony® PCS-HG90	Satisfactory	JVCS not HD capable	No	Yes(1)
Sony PCS-XG80	Few problems	Some Lip Synchronisation problems	No	Yes
Tandberg 990 MXP	Satisfactory	Satisfactory	No	Yes

Tandberg Edge 95MXP (2008)	Problems connecting to LifeSize Codec	Satisfactory	No	Yes(2)
Tandberg Profile 600MXP	Minor problem	Satisfactory	No	Yes (1)
Tandberg FieldView™	Some problems	Not compatible as SIP not currently supported	No	Yes
Tandberg C60	Some problems	Lip Sync problems	No	Yes
Tandberg C20 Plus	Some problems	Satisfactory	No	Yes
Tandberg C40	A minor problem	Satisfactory	No	Yes
ZTE ZXT500	Some problems	Satisfactory	No	Yes
	With Another CODEC	Multipoint Conference through JVCS	MCU Control	Far End Camera Control

About this table

** For further details of the specific problems experienced refer to the individual product test reports

1. Far-end camera control and remote source selection.

4. IMPORTANT FACTORS/CONSIDERATIONS

GENERAL

The first product evaluation took place in 1997 the latest in December 2012 the technology has improved significantly during this period, so it is unrealistic to compare products directly

unless they were tested at a similar date. There is an inevitable delay between the arrival of a new product to the marketplace and a VTAS evaluation so it is strongly recommended that the manufacturers' web sites be consulted to obtain current product information.

4.1 Ease of Use

Most of the products now being tested are very easy to operate. Manufacturers have devoted considerable effort to improving this aspect of performance. Unfortunately some products still demand considerable effort to install, requiring assistance from technical staff. The test reports highlight difficulties encountered.

A web-based interface for diagnostics and set-up is now provided by several products. This can be a real asset as software updates can easily be downloaded and suppliers can interrogate the system to fault find. With this facility, units in remote parts of the campus can also be monitored from a central area manned by technical staff.

4.2 Value for Money

The packaging of products can sometimes be misleading. For this reason the less expensive modest looking set top CODEC should not be rejected on appearance alone. Some of these 'portable' units incorporate all of the features of much more costly room based systems, and in many cases will meet most needs admirably.

For personal use, videophones such as that marketed by Motion Media may be an option as they are much less cumbersome than a PC based system and can allow a PC to be used independently perhaps for data exchange during a conference. Such products are outside the scope of this document, but may be worthy of independent investigation.

4.3 Multi-vendor Solutions

It is unusual for a single manufacturer to have a broad enough capacity to provide all of the components of a videoconference system. As a consequence it is common practice for CODEC manufacturers to incorporate third party components e.g. cameras, microphones, echo cancellers and picture monitors within their products to achieve a state of the art package.

4.4 High Definition Capability

High definition videoconferencing products using wide screen formats, e.g. 1920 x 1080 pixels at 30 fps and 1280 x 720 pixels at 60 fps. are now being marketed and have become the norm with both mainstream players and some smaller specialists offering products. Several manufacturers now offer high definition capability to the second H.239 Content channel to support dual HD channel conferencing.

4.5 Widescreen Formats

High Definition (HD) television systems display images in a 16:9 widescreen format as opposed to the 4:3 (width:height) aspect ratio images of normal definition television. One digital widescreen format that uses progressive (p) scan techniques to construct the image and has a vertical resolution of 720 television lines is known as w720p. This format has a resolution of 1280x720 pixels. Another format, known as w448p, resolves 768x448 pixels. The w228p widescreen format only has a resolution of 512x288 which is less than VGA (640x480) so, although wide screen, it does not qualify as high definition.

4.6 Television Scanning and Aspect Ratios 720i, w1080p etc.

A “w” prefixing the resolution e.g. w720 indicates that the signal is transmitted in a widescreen format of aspect ratio 16:9 rather than the old analogue aspect ratio of 4:3.

An “i” following the resolution figure e.g. 1080i indicates that the transmission is interlaced scan. This is the analogue format where the picture is transmitted as two fields superimposed. One field contains only odd numbered TV lines e.g. 1, 123, 527 etc. and the other only even lines such as 2, 124 and 528. Interlaced scanning enables a picture to be effectively transmitted in a smaller bandwidth. A “p” following the resolution figure i.e. 720p indicates that the signal is progressive scan. In progressive scan there is no interlacing of fields as the picture is scanned sequentially line after line until the end of the frame.

Interlaced scan can introduce flicker with some signals whereas progressive scan can reduce the flicker to a negligible amount.

4.7 Interlaced CIF (iCIF)

The Common Interface Format (CIF) is a part of the H.261 standard that defines the vision signal. It enables videoconferencing communication between American NTSC television systems and European PAL systems without standards conversion. CIF, sometimes termed Full CIF to differentiate it from Quarter CIF (QCIF) achieves compatibility by combining elements of both TV systems. It requires 352 (horizontal) by 288 (vertical pixels) at a repetition rate of 30 TV frames/second. The refresh or repetition rate can be doubled to 60 frames/second by interleaving a second frame in between the horizontal pixels of the first frame. This is termed interlacing. Interlaced CIF or iCIF utilises 352 horizontal by 576 vertical pixels at 60 frames/second and greatly improves the quality of moving images.

VIDEO

4.8 Video Coding

H.261 was the original video coding specified by the ITU to ensure compatibility between different manufacturers' products. It still remains the base coding across ISDN and IP networks to ensure communication between products should other coding algorithms prove incompatible. To improve results especially at low bandwidths H.263 coding was introduced and further enhanced through H.263+ and H.263++. The latest development, H.264 coding, is designed to give good results with a saving in bandwidth, and has now been adopted by most manufacturers.

H.264 SVC coding allows automatic scaling to optimize resolution, frame rate and overall quality dependant upon the capabilities of the transmission path and the end point decoder

4.9 Dual Video Streams

Dual video streams are now a feature of several CODECs. This enables simultaneous transmission of both participants and content (e.g. the output from a document camera). There has to be a compromise to fit both signals in the same pass-band. Systems normally allow user definition of the bandwidth allocation between streams to optimise the chosen information. Where manufacturers provide an MCU as part of the CODEC package, dual video streams (people and content) may be supported between compatible units, such as the Polycom VSXT series CODECs. The ITU-T standard H.239 was created to achieve dual video stream compatibility between different systems and is now implemented by most

manufacturers.

4.10 Picture Optimisation

Several manufacturers provide intelligent picture optimisation. When a static picture from, for example, a document camera is being transmitted the CODEC will ramp up the resolution to 4CIF at the expense of movement rendition. When however movement is important, e.g. a moving video sequence, then resolution is reduced to the normal CIF, but coding is optimised to reproduce good movement.

AUDIO

4.11 Audio

The JVCS Management Centre, located at Edinburgh, offers MCU facilities to registered users for establishing multi-site conferences. To ensure sites can conference effectively they are all required to pass a regular Quality Assurance (QA) test before being registered as a user of the JVCS MCUs. This QA test covers many aspects of performance but a critical parameter is the audio level received at the Management Centre from an individual site. Unfortunately several site CODECs have in the past been unable to meet this requirement and the low audio level has caused some failures. For point-to-point conferencing between identical units this should not cause a problem but, when multi-conferencing through an MCU, large level differences between sites can seriously degrade the audio quality and could affect echo canceller performance. JVCS MCUs can accommodate and equalise these level differences, however this does not guarantee that the site will pass the QA test.

Echo cancellers (ECs) are now an integral part of most good quality videoconferencing systems and are almost entirely automatic in operation, requiring no setup by the installer. The majority function efficiently in a conference room environment. When conferencing from a large lecture theatre is envisaged, the control of echo is much more difficult and a separate EC with a wider window of correction may be required. In this case it is essential that the conferencing system can provide the necessary input and output connections to allow an external EC to be introduced. Not all CODECs permit external ECs. Some CODECs are provided with a separate EC for each microphone and manage difficult environments very efficiently, so it is certainly worth checking their operation in the intended room before purchasing a separate echo canceller. For small groups (two to three people) a single microphone (or microphone unit) will be adequate. For larger groups additional microphones will be needed to ensure good sound pick up. The conferencing system should be able to accommodate additional microphones easily and/or provide for an external audio mixer to be connected to enable this. See the VTAS guide, Videoconferencing Audio and Video Equipment, for further details.

4.12 Audio Coding

Advanced audio coding (AAC-LC, AAC-LD).

An appreciable delay on the audio is experienced during most H.320 and H.323 conferences. To alleviate this, Advanced Audio Coding has been introduced by several manufacturers. This improves sound quality for low bit rate transmission. The basic interpretation, AAC-LC, extends the upper audio frequency response to around 16kHz in comparison with traditional audio CODECs which deliver 3.5 or 7kHz audio frequency response. The more advanced interpretation, AAC-LD, also reduces transit delay during the coding process. For example,

AAC-LC has a typical delay for a 64kbit/s data stream of around 130ms. AAC-LD reduces this to nearer 20ms and, as such, enables high quality audio up to 20 KHz for music and speech with a low transit time delay.

G.728 Audio Coding

A low delay coding that requires 16 Kbit/s for its transmission

G.729 Audio Coding

A bandwidth saving coding that gives a comparable quality to G.711 (64 Kbit/s) but only requires 8 Kbit/s of bandwidth

NETWORK

4.13 IP Video Tests

IP videoconferencing has developed into an established form of communication. Both the Welsh Video Network (WVN) and the Scottish universities network, known as SMVCN, rely on this method of connection for their day to day conferencing activities. Where adequate bandwidth is available it is better than ISDN as a means of connection. Local bottlenecks can however still compromise quality when competing data can disrupt the sound and vision signals. The growth in use of IP-based conferencing systems has influenced the products now offered. In the past ISDN H.320 CODECs were the norm, with IP (H.323) functionality available as an option. The situation is now reversed, with most products now offering IP/H323 as the basic configuration with only a few products offering ISDN functionality as an option.

4.14 Network/Dialling

All H.320 or H.323 compliant products should be capable of communicating effectively. For identical products this is certainly the case but some problems still remain when conferencing between dissimilar equipment. Generally these problems are fairly minor (as detailed in the test reports) and can involve little more than resetting some menu options. This does demonstrate, however, the importance of always having a trial run before a conference with a new site. As no difficulties in dialling overseas with ISDN CODECs have been encountered in testing since 1999 this test is no longer conducted. During an ISDN-6 (384kbit/s) connection it is not uncommon to lose one of the lines through congestion or fault conditions on the network. When this happens most systems now carry on conferencing, albeit at a lower data rate. IP systems generally reconnect quickly if the connection is broken momentarily.

4.15 Session Initiation Protocol (SIP)

In basic IP transmission a digital signal may be coded into several data streams that can each take different routes before arriving at their destination. This means parts of the data can arrive at different times. For most IP traffic this does not cause a problem as the original signal may still be decoded accurately. For digitised audio and video over IP, all the data has to arrive at a similar time i.e. it has to take the same route, otherwise the original signals cannot be reproduced accurately. SIP is an international standard that aims to achieve this.

4.16 Dynamic Host Configuration Protocol (DHCP)

For devices such as PCs and videoconferencing CODECs to communicate over an IP network they normally require a dedicated address - these addresses need to be known in

advance by each endpoint for communication to be established.

As an Internet Service Provider (ISP) may have thousands of individual customers, rather than allocating a dedicated address to each customer a dynamic system of addressing is frequently used. Each time they log on, a customer is assigned one of a batch of addresses held by the ISP, so they may be using a different address every time.

To enable the network to track and route dynamic addresses the appropriate software has to be in place at each terminal and throughout the network.

DHCP allows dynamic addressing by automatically sending a new IP address when a computer is plugged into a different place in the network.

Videoconferencing products are now being marketed for use over DSL home connections via an ISP, and it is essential that these CODECs support DHCP.

4.17 802.11 b/g Wi Fi

The IEEE standards for Wi Fi wireless networks. It was originally conceived as IEEE standard 802.11 b with a bandwidth of 11 Mbit/s but the later “g” version has increased bandwidth and is back compatible with the “b” version.

4.18 API Commands

Most CODECs are capable of interfacing to room control systems. Normally this is achieved through an RS.232 serial connection but some CODECS use an IP interface and API commands to connect with the room. API is a particular command structure that is used widely throughout IP networks, mobile phone networks etc.

4.19 BFCP Binary Floor Control Protocol

A protocol developed by Cisco Systems Incorporated for controlling the access to media resources in a conference. For more information see:

<http://www.cisco.com/en/US/docs/routers/asr1000/configuration/guide/sbcu...> [4]

4.20 SSH Secure Shell Protocol

As most IP networks are basically insecure SSH provides a method of sending/receiving data securely between two PCs. Initially devised to enable secure Logins to a server it may be used where a secure connection is necessary e.g. the remote configuration of a videoconferencing system. In this case both the CODEC and the remotely connected PC must be running the appropriate SSH software for secure data transmission to occur.

DATA TRANSFER

4.21 Data Transfer/Application Sharing

Early attempts at data conferencing over ISDN, usually involved interleaving the data within the overall videoconferencing passband. These systems were reliant on the ITU-T T.120 recommendations for transmission. While T.120 did guarantee data exchange independent of platform or system, it did have some limitations when used within low data rate conferencing systems (e.g. 128kbit/s, ISDN 2), as the data would degrade the conference video images. To minimise this effect the T.120 data exchange rate was limited to 19.2 or

38.4kbit/s, but this limitation proved far too slow for large software programmes such as Microsoft PowerPoint and so other methods are preferred and T.120 is now mainly redundant.

A separate channel is now used for the data. Either the Internet or the second channel provided by CODEC's with dual video, leaving the main conferencing channel intact. Simultaneous audio/video conferencing together with the data are thus transmitted and received and is much more successful for teaching purposes.

Some CODECs provide a VGA / SVGA/XGA IP connection to allow the screen output from a PC or laptop to be transmitted to a remote site. This image may be transmitted in native SVGA/XGA resolution or converted to CIF or 4CIF. The transmission of the PC image either replaces the video image from the system camera or occupies a second video channel (Dual video systems). Some manufacturers enable an internet connected PC to transfer images into a conference without a direct physical connection to the CODEC. Polycom's People + ContentT IP for Windows, Tandberg's Soft Presenter option using Virtual Computing Network (VCN) server software and LifeSize's Virtual Link all use this method. These methods enable data exchange to occur but do not enable data sharing between sites.

FEATURES

4.22 On Board Multipoint Control Units (MCUs)

Several manufacturers now offer on board MCU facilities, and some offer internal MCUs with mixed H.320 and H.323 working, which some sites may choose to investigate. Testing is outside the remit of these evaluations. The VTAS evaluations do not include a full investigation of internal MCUs but only a brief appraisal of their operation. Cascaded MCUs are not part of the H.323 standard.

4.23 Remote Camera Control/Source Selection

Far end (or remote) camera control (i.e. control of the camera at the remote site from the local site) is a common feature, but was initially only available for H.320 systems. Functionality over H.323 systems is now commonplace. Remote source selection i.e. selection of the remote sites camera, Visualiser, PC, etc. from the local site is also a feature on several CODECs. These facilities may not operate through an internal or standalone MCU.

4.24 Auto Tracking Cameras

Early attempts at auto tracking cameras were not effective, but the technology has improved so that the better systems are now a real asset during a conference. They enable accurate and effective camera framing of the participants speaking, by locating the source of their voice. This avoids manual camera adjustment and is a definite bonus for new conference users.

4.25 Encryption


To provide a measure of security to a conference the transmitted data may be encrypted. Two encryption algorithms are currently in use:

- Data Encryption Standard (DES) with a 56 bit session key.
- Advanced Encryption Standard (AES) with a 128 bit session key.

4.26 Picture on Picture (Chroma-Key)

To produce an artificial background for a presenter, e.g. the BBC weather presenter viewed

against a background of a weather map, a technique termed “Chroma-Key” is used. A coloured or “chroma” switching signal is used to switch between the background (weather map) and the foreground (presenter). This is achieved by placing a plain coloured background (e.g. a large green card) behind the presenter to produce the switching signal. The image from the presenter camera includes the presenter in the foreground with all other parts of the image being green. The “Chroma-Key” device has two inputs, the presenter camera image which provides the switching signal and the desired background e.g. the UK map from another camera or PC image etc., it then electronically processes both images to effectively replace the green areas of the presenter camera image with the corresponding areas of the map. It is a most useful technique but great care is needed in lighting the presenter and the background green screen to achieve good results. All too frequently there is a shimmering effect around the presenter that can be most distracting. Polycom™ call the process Picture on Picture in their HDX8000 series CODECS.



Example of Chroma-Key or Picture on Picture with a presenter superimposed on a background image of a PC monitor.

4.27 High Bandwidth Digital Content Protection (HDCP)

HDCP is a copy protection system that prevents unauthorised copying of high definition material between replaying sources e.g. a DVD player, to the receiving display device. It is only present on digital interfaces e.g. DVI or HDMI. Essentially an encryption system it is increasingly being used to prevent pirate copying. Without HDCP a display monitor will only be able to display a lower resolution picture from material thus encoded. So for future full high definition compatibility, picture monitors require to be both HDTV and HDCP capable.

INTERFACES AND CONTROL

4.28 Digital Video Interface (DVI)

The transfer of picture information from a PC to its visual display unit (VDU) or picture monitor has in the past always been achieved through the VGA interface. The VGA interface used analogue signals, so the digital picture information from the PC had to be converted into its analogue equivalent to enable the cathode ray tube (CRT) based VDU to display the images. This is because the CRT is an analogue device that requires analogue Red Green and Blue component signals to operate. With the advent of flat panel LCD and similar display devices that are basically digital in operation the digital to analogue conversion to VGA and the subsequent analogue to digital conversion for the LCD device introduced unnecessary signal processing and degradation. The DVI interface avoids this by transferring picture information directly in the digital domain.

4.29 Analogue Component Interface YPbPr

Some television/PC equipment is provided with Analogue Component (YPbPr) outputs for system connection. These component interfaces comprise three separate signals: The black and white or Luminance signal (Y), and two PAL colour difference signals Pb and Pr. As the information is carried on three separate signals rather than the single signal of Composite video the quality is higher. Composite video involves extra signal processing to

combine the components into a single signal, Component video avoids this complication. The drawback is that all connections between equipment requires three separate cables as opposed to one with Composite.

4.30 Extended Display Identification Data (EDID)

When a display device is connected to a PC unless the PC is aware of the capabilities of the display it will be unable to optimise the signal to produce the best results. The Video Electronics Standards Association (VESA) introduced a system that enables the PC graphic card to identify the type of display monitor connected and so adjust the scan rates and colour depth to produce the optimum picture. Without EDID the PC would default to basic values and may produce a display of the wrong size and aspect ratio. A CODEC with EDID on its PC input will be more accurate at displaying VGA images.

4.31 The Sony Philips Digital Interface (SPDIF)

To overcome the signal processing necessary to digitise analogue audio signals in the transmission chain Sony and Philips have introduced the SPDIF interface. This digital interface based on an RCA plug/socket enables the audio paths of video equipment to be connected together in the digital domain.

4.32 VISCA

VISCA is a proprietary camera control protocol used by Sony to control its PTZ range of videoconferencing cameras. It utilises R232 serial connections to enable several cameras to be daisy chained to a remote control for convenient operation.

5. TRADEMARKS AND ACKNOWLEDGEMENTS

5.1 Trademarks

Aethra Vega Star Gold, Aethra Vega X3 and AePPTManager are trademarks of Aethra.

AVermComm H300 and Avermedia HVC330 are trademarks of AVermedia Global

Cisco Telepresence EX60 and Cisco SX20 Quick Set are trademarks of Cisco Systems

Gentner and V-There 2200 are trademarks or registered trademarks of ClearOne Communications Inc.

LifeSize Room, LifeSize Team, LifeSize LGExecutive , LifeSize Passport,

and *Lifesize –Team22 0*are registered trademarks of LifeSize Communications.

Microsoft NetMeeting and Microsoft PowerPoint are registered trademarks of the Microsoft Corporation.

PictureTel, Polycom iPower, Vortex, Polyspan, Viewstation ,V500, QDX 6000, Polycom® StereoSurround™ , HDX 9004™ HDX 4500™ are trademarks or registered trademarks of Polycom Inc.

Sony Contact are registered trademarks of the Sony Corporation, Japan.

VBrick is a registered trademark of VBrick Systems Inc.

VCON, MediaConnect and ViGO are registered trademarks of VCON, Ltd.

Zydacron and OnWAN are registered trademarks of SCOTTY Tele-Transport Corporation Inc.

5.2 Further Acknowledgements

The following manufacturers/suppliers generously made their products available for the evaluation and were most helpful during the testing.

Aethra Review Video Gibson Videoconferencing Ltd	- Aethra Vega Star Gold
AuDeo Systems Ltd.	- Polyspan ViewStation
AVermedia Global	AVerComm H300 Avermedia HVC330
Call2View	- Tandberg 6000
Cisco Systems	-Telepresence EX60 Cisco SX20 Quick Set
Codian Ltd	- Codian IP VCR 2210
First Connections	- Polyspan FX
Gentner Communications	- V-ThereT 2200 CODEC

LifeSize Communications NuVideo	<ul style="list-style-type: none"> - LifeSize RoomT - LifeSize TeamT - LifeSize Express -LifeSize Room 200 -LifeSize Passport LifeSize LGExecutive <i>Lifesize – Team220</i>
McMillan UK Ltd	<ul style="list-style-type: none"> - Tandberg 800
MVC UK	<ul style="list-style-type: none"> - Tandberg 500
Pinacl	<ul style="list-style-type: none"> - PictureTel 680 4P - PictureTel 970
Polycom UK	<ul style="list-style-type: none"> - Polycom iPowerT 9800 - Polycom Vortex EF2241 - Polycom VSXT 7000 - Polycom V500T - Polycom VSXT 8000 - Polycom HDX 9004 - Polycom RSS 2000 - Polycom HDX8004 -Polycom QDX 6000 Polycom HDX 9004 Polycom HDX 4500
Questmark	<ul style="list-style-type: none"> - Aethra Vega X5 - Aethra Vega X3

Radvision	Radvision Skopia XT1000
	Radvision Skopia VC240
	Radvision XT5000
Review Video	- ZTE ZXT500
Satelcom UK Ltd	- VCON Quickconnect
Sony	<ul style="list-style-type: none"> - Sony Contact 6000 - Sony PCS-1P - Sony® PCS-HG90 -Sony PCS-XG80
Tandberg UK Ltd	<ul style="list-style-type: none"> - Vision 800 and 5000 - Director System - Tandberg 6000 with H.264 - Tandberg 990 - Tandberg 3000 - Tandberg 990 MXP - Tandberg Profile 600MXP - Tandberg Content Server - Tandberg FieldView - Tandberg Edge 95 MXP(2008) Tandberg C60 Tandberg C20 Plus Tandberg C40

The UK Office	- VBrick 6000
VBrick Systems	- VBrick 3000
VCON UK	- VCON ViGO - VCON MediaConnect 9000
VideoCentric Ltd	- VCON HD5000
VTEL Europe Ltd	- VTEL TC1000/2000
First Connections	- Zydacron OnWAN Z340

The manufacturers have been invited to comment. A full list of the responses is available

Source URL: <https://community.jisc.ac.uk/library/advisory-services/codec-test-procedure>

Links

[1] <http://www.ed.ac.uk/is>

[2] <http://www.ja.net/documents/services/video/testprooutline.pdf>

[3] <http://www.ja.net/services/video/vtas/archive.html>

[4] http://www.cisco.com/en/US/docs/routers/asr1000/configuration/guide/sbcu/sbc_BFCP.html